

SPARK 130


- Welding unit with inverter technology piloted by microprocessor.
- The arc dynamic of the product is unique and revolutionary on the market.
- Can be used with all types of electrodes: rutile, basic, stainless steel, cast iron in direct current.
- Very handy, thanks to its small weight (2.9 kg), its highly reduced volume and its very low consumption.

■ MMA

- ✓ Immediate start thanks to its very high no-load voltage
- ✓ Constant welding power
- ✓ Very smooth melting due to the direct current.
- ✓ Insensate to supply current fluctuations or to the arc length.
- ✓ Very good penetration and perfect arc stability.

■ ASSETS

- ✓ **ARC FORCE** : punctual increase of current in difficult welding situation.
- ✓ **HOT START** : increased power at start
- ✓ **ANTI STICKING** : anti sticking process.



- Delivered in bundle with:
- Earth cable (1,6m/ø16mm²)
 - Electrode holder (2m/ø16mm²)
 - Techno 11 helmet

LCD TECHNO 11

High quality LCD: UV/IR DIN 15 protection
Field of vision : 98 x 35 mm

Total weight: 400 g

Power supply: Solar

Filter:

- Initial shade : 3
- Welding shade: 11
- Arcing reaction time ≤ 0.6 ms
- Ideal for MMA/MIG-MAG/TIG : from 10 to 200 A



50/60hz	-AM-	I ₂	min▷max							EN60974-1 (40°C)		U ₀	 cm/kg	 Protected & compatible POWER GENERATOR (+/- 15%)
				ø1.6	ø2	ø2.5	ø3.2	ø4	ø5	I _A (60%)	X% (I ₂ max)			
230V 1~	13A	10-130A	20-200A	62	50	47	24	-	-	45A	5%	80V	10x17x25 2.9	4 kW 5.0 kVA