

The NEOMIG 150 is a semi-automatic machine that combines MIG/MAG, cored wire and MMA welding processes. Thanks to its user-friendly interface, the voltage and wire speed settings are made easier. Ultra-light, it is easy to carry around. The NEOMIG 150 is recommended for welding steel, stainless steel and aluminium.

3 in 1


- MIG-MAG GAS
- MIG-MAG NO GAS
- MMA



Ultra-light and portable

- 9.6 kg weight.
- Ergonomic handle.

Easy set up



- Voltage set selection from 15 to 21 V.
- Wire speed selection from 3 to 10 m/min.

Sturdy build quality

- Reinforced mechanical structure.
- Pads for shock and vibration absorption.

Integrated wire feeder

- Ø100 (1 kg) wire reels.
- Ø200 (5 kg) wire reels.
- 2 rollers motor
- Supplied rollers :
 - steel : 0.8
 - no gas : 0.9

MIG/MAG Torch

- Supplied with a removable torch 150 A - 2.20 m fitted for steel.
- EURO torch for a fast assembly/disassembly.

Simplified display



- 2 colour LED to display :
- Thermal protection.
 - Power up.

MIG/MAG - MMA

- Wire diameter Ø 0.6 mm to 0,8 mm.
- Électrode Ø 1.6 mm à 3.2 mm.

Polarity reversal cable

- For NO GAS welding.



Features



Inverter technology to ensure an excellent welding current quality and a low electric consumption.



Can weld rutile electrodes . Antisticking (prevents electrode sticking at start).



Can weld :
- MIG/MAG wire with gas
- MIG/MAG cored wire without gas

NO GAS ready to weld

This process allows to :

- Weld with cored wire thanks to polarity reversal.
- Ignore perturbations due to the exterior environment (wind).
- A better portability thanks to the absence of gas bottles.
- Ideal for outside work on thin metal sheets.

Includes

- **Earth clamp** (cable 1.6 m / 16 mm²)
- **Electrode holder** (cable 1.6 m / 10 mm²)
- **Accessories bag**
 - Contact tip 0.9 mm.
 - Gas nozzle « no gas ».
 - Tightening key for contact tips.
 - Gas tube 1 m.
 - 2 clamps for the gas tube.

50/60hz	MMA I ²	min▷max 30▷140A	Ømm		100	200	Electronic Control	équipé d'origine / original equipment / originalausstattung / equipamiento de fabrica		EN60974-1 (40°C)				cm/kg 40x20x33 / 9.6	Protected & compatible POWER GENERATOR (+/- 15%)
			GAS	NO GAS				Ømm	Ømm	MIG	MMA				
230V 1~	16A	20▷120A	0.6 - 0.8	0.9	✓	✓	0.8 - 0.9	0.8	I _A (60%) 80A	X% (I ₂ m ₂ x) 140A 15%	I _A (60%) 70A	X% (I ₂ max) 120A 15%	8 kW		